

January 29, 2001



**YA502MP**  
includes 13 fittings



**YA502P**  
10 included in  
YA503MP



**YA502FC**  
**with flow control**  
3 included in YA503MP

## Avoid fighting air hoses!

Display card shows off patented double 360° swivel fittings. Swivels available with or without regulator.

### Master Pack includes:

- Ten (10) swivel fittings ..... YA502P
- Three (3) swivel fittings with flow Control ... YA502FC
- FREE display card
- FREE display 6" hose

### Features:

- Patented universal joint improves maneuverability, minimizes fatigue and extends hose life.  
(Patent No. D-295,552; D-295,553; D-317,818)
- 360° swivel at two points allows the hose to fall freely providing superb tool control.
- Lightweight, non-marring composite construction for improved tool control and long swivel fitting life.
- Flow control model (YA502FC) is ideal for buffing & polishing applications.
- Knurled flow control knob is easily adjusted & conveniently located.

### Specifications

YA502P (No flow control)  
Airflow: Up to 33 SCFM (935 LPM)

YA502FC (Flow control)  
Airflow: Up to 46 SCFM (1,303 LPM)

Pressure Drop (YA502P & YA502FC)	
Flow SCFM	Pressure Drop PSIG
5	1
15	4
20	7
25	13
35	23

**WARNING**

- Wear safety goggles (operator and bystanders).
- Wear hearing protection (operator and bystanders).
- Avoid prolonged exposure to noise.
- Read instructions before using power tools.



- Avoid prolonged exposure to vibration.
- Avoid breathing power tool exhaust.
- Do not exceed 150 PSI (10.3 Bars).