

February 12, 2001

Snap-on



LISTED
333M

**12V, 0-20 Amp. Automatic Battery
Charger with Deep Discharge Recovery**
for reconditioning and maintaining 12 volt flooded
and sealed batteries.

Features:

- Advanced microprocessor control
- Select “FLOODED BATTERY” or “SEALED BATTERY” with the flip of a switch
- Deep discharge recovery technology
- Lights indicate:

Red - Power

Yellow - Charging (blinks to indicate battery is near end of charge and is in Charged/Float Mode)

Green - Proper polarity (blinks to indicate charge is complete and is in standby mode)

Alternating Green & Yellow (flooded batteries only) - Indicates first stage of deep discharge recovery process

- Cooling fan is activated when charging current exceeds 8 amps



YA1222

Specifications:

Input 120V 60Hz, 4.5 AMPS

Output 20 AMPS@13.02V

Cable Length 6 ft (1.8M)

Power Cord Length 6 ft (1.8M)

Overall Dimensions:

Height (to top of handle) 8.0" (203mm)

Width 10.62" (270mm)

Depth 8.0" (203mm)



WARNING



Wear safety shield (user & bystanders).



Charger must be OFF when connecting or disconnecting leads.



Keep flames and sparks away from batteries.

new product