

February 26, 2001

Hazardous-Duty Explosion Proof Fluorescent Lamp

In addition to the required degree of safety, ECU5000 assures ease in handling and maintenance as well as reliable, long-lasting operation.



For environments where potentially explosive dust, vapors or gases might be present.

- refineries
- steel mills
- grain elevators
- aircraft hangers
- commercial garages
- chemical processing facilities
- below ground service pits



U.L. Listed and CSA Certified for Class I, Division I, Groups C & D (flammable gases & vapors), and Class II, Division I Groups F & G (ignitable dust).

OSHA compliant with regulations 1910.307(b) and 1926.407(b) (when used and maintained properly)

Specifications

- Bulb 26 watt, 120V, 50/60Hz, Fluorescent
- Cord 1090-Hz w/ 16-3 SOW-A
- Cord Length 24', 7 "
- Plug .. NEMA 5-15 non-hazardous duty
- Lamp Dimensions with hook Overall length 19.25" O.D. 4"

Features

- Non-sparking aluminum guards
- Shock-resistant tempered glass globe
- Ribbed anti-slip aluminum handle
- Rubber bumper guards
- Swivel hook
- Made in USA

ECU5000



WARNING



- Do not remove or by-pass the grounding prong in any electrical plug.



- Disconnect power before servicing.
- Read & follow instruction manual.

Snap-on

new product