

May 21, 2001

Blue-Point

ORDER: YA692A

7 Ton Capacity **Value Priced**
Air-Operated End Lift

**Truck & Bus
Maintenance Shops
Truck Repair Shops**



YA692A

Features

- Dual hydraulic dampers smooth operation and provide safety restraint if load is suddenly removed
- Two (2) stage air valve permits lifting speed selection
- Heavy duty wide base provides excellent stability and strength
- Six (6) inch spring loaded front caster permits full mobility and realignment of jack prior to load contact
- Ten inch pneumatic rubber rear wheels make maneuvering easy
- Saddles rotate in 90° increments for bumper or frame lifting
- Ten saddle height adjustments
- Telescoping lifting arms facilitate lift position adjustment and compact storage

Specifications:

Capacity	7 tons
Low Height	13.50"
High Lift Point	58.50"
Power Raise	32.50"
Saddle Spread	29" to 41"
Minimum PSI for Rated Load	200
Clearance (Lifting Column to Front of Saddle)	13.00"



WARNING

- Wear safety goggles. (User & bystanders)
- Do not work on vehicles supported by jack; use jack stand.
- Do not work on vehicles than rated capacity of jack.
- Use jacks on hard, strong, & level surfaces.
- Read & follow instruction manual.