SNAP-ON SECURITY LINK

Using compatible diagnostic tools, now you can seamlessly connect to secure vehicle gateways

Snap-on.

CONNECTING YOUR DIAGNOSTIC TOOL FOR USE WITH SECURE VEHICLE GATEWAYS

What you need:

- A compatible Snap-on diagnostic tool with Wi-Fi access
- An authorized AutoAuth account(s)
- A Snap-on® Profile Manager Account

Watch the Getting Connected video @

SNAPON.COM/SECURITYLINK

GETTING YOUR DIAGNOSTIC TOOL INFORMATION

Make sure your diagnostic tool is connected to Wi-Fi before you start!

You'll need some information from your diagnostic tool. Select "System Settings or Tools", then "Get Connected".



| Pin Code: | | |
|--|--|---------|
| Activation Code: | | |
| Oet Connected ← Back | | |
| Get connected! | er secured dis | |
| What you'll need > Device details (serial number, etc.) > CEM account(s) for source whole gateways > A Size on sorbits to manage exemption | Device details Serial Number: 123/ADC456789 PN Code: 686989 Activation Code: 68698989 | |
| Add device details to your Snap-on Profile* | | 3 |
| profilemanager.mitchell.com Link your device and OE Profile | (M account(s) by adding device details and account info to your | Snap-on |

Device details... Serial Number: 123ABC456789 PIN Code: 888888 Activation Code: 88888888

CREATING AN AUTOAUTH ACCOUNT

NOTE - AutoAuth charges an annual fee.

Make sure your diagnostic tool is connected to Wi-Fi before you start!

Go to autoauth.com and select "Register Now" and create an account.




Remember your Username and Password.

2 Check your email and verify your account.

Login to autoauth.com and follow the link to complete your registration as a "Service Center Signup / Independent Technician Signup".

After entering the required information select "Sign Up".

Select the "Manage Tools" tab and enter the required information.



When done select "Add".

Add

Your AutoAuth account is now complete.

GREATING A SNAP-ON PROFILE

A Snap-on Profile Manager account is required to complete the process. If you already have a Profile Manager account, log in and go to Step 3.

(You would have a profile manager account if you have previously accessed SureTrack® community or ALTUS Drive)


To create a Profile Manager account, go to profilemanager.mitchell1.com.







Login to your account and select the "Device Management" tab.



Enter your **Diagnostic Tool Pin Code** and **Serial Number** from the Get Connected screen of your Tool (See Step 1 at the beginning of these instructions).

4

Select the "Security Link" tab, then select "Add Secure Credentials".



Enter your "AutoAuth" account username and password and select "Save".

5

Your Diagnostic Tool is now linked to your AutoAuth account allowing you to access your Secure Vehicle Gateways.



Note - Autorization Key is not needed.



SNAP-ON® SECURITY LINK™

Using compatible diagnostic tools, now you can seamlessly connect to secure vehicle gateways

Snap-on is a trademark of Snap-on Incorporated. All rights reserved. ©Snap-on Incorporated 2022. EAZ0042L62C Rev. A

US

